

**suprema**

# BioMini Combo

Contact Smart Card Reader with USB Fingerprint Scanner

Contact Smart Card Reader for Stronger Authentication

Reliable Capturing Performance Under Direct Sunlight Up To 100,000 Lux

Advanced Live Finger Detection (LFD) Technology

FBI PIV and Mobile ID FAP20 Certified Image Quality

Ergonomic and Stable Design



**| BioMini Combo |** BioMini Combo has specially been designed to provide a high level dual-authentication security solution for PC based identity access management solutions. Housing with contact smart card reader, BioMini Combo provides the latest 500dpi slim optical sensor, which boasts a large platen size for easy and reliable fingerprints capturing as well as Suprema's advanced LFD (Live Finger Detection) technology.

BioMini Combo maintains the highest standards and has both FBI-PIV and mobile ID FAP20 certifications which enable users to capture any types of fingerprints even under direct sunlight environment. Combining with its comprehensive SDK solution, BioMini Combo offers superior hardware and software compatibilities which could be an ideal platform for developers.



# suprema BioMini Combo

Contact Smart Card Reader with  
USB Fingerprint Scanner



## BioMini Combo Features



- NIST certified interoperable image & template format standards (ANSI-378 / ISO 19794-2, ISO 19794-4)
- Image Compression Standard (WSQ)
- FBI PIV/FIPS 201 and FBI Mobile ID FAP20 certificates



- Advanced Live Finger Detection (LFD) Technology



- World's best performing fingerprint algorithm : Top results in NIST MINEX tests and FVC
- Template extractor and matcher
- Fast matching speed : 100,000 match / second (with Intel Core 2 Duo)



- USB 2.0 High speed interface
- Supports multiple device handling
- Automatic finger placement detection
- Ergonomic indication LED



- 500 dpi optical fingerprint sensor
- Large Platen Size : 0.71" X 1.0" (18.0mm x 25.4mm) (FAP20 standard: 0.6" x 0.8")



- Compliant with ISO 7816 Contact Smartcard and EMV 2000 version 4.1
- Transmission rate : 2 Kbps to 500 kbps
- Supports 5V (55mA), 3V (50mA), 1.8V (20mA) Smart Card
- Supports SAM Slot (Optional)



- BioMini SDK for easy application software development
- Supports MS Windows / Linux
- Supports multiple programming languages : VC++, VB, C#, VB.NET, Java
- Multi-threaded code design fully utilizing multi-core CPU power



- Works under direct sunlight

## BioMini Combo Specifications

Fingerprint Sensor	Optical
Resolution	500 dpi / 256 gray
Platen Size	18.0mm x 25.4mm ( 0.71" x 1.0" )
Sensing Area	17.0 x 25.0 mm ( 0.67" x 0.99" )
Image Size	320 x 480 pixels
Interface	USB 2.0 High Speed
Operating System	Microsoft Windows / Linux
Operating Temp.	-10 ~ 50°C
Humidity	90% or less RH, noncondensing
Certification	CE, FCC, KCC, UL, WHQL, USB-IF, WEEE
Smart Card	ISO 7816 and EMV 2000 Contact Smart Card with SAM Slot (Optional)
Size ( W x L x H )	95.7 mm x 114.8 mm x 52.6 mm

## BioMini Combo SDK Specifications

Template Size	1024Bytes (Configurable)
Enrollment Time	< 0.1 second
Verification Time	< 0.1 second
Identification Time	100,000 matches / second ( with Intel Core 2 Duo )
Programming Languages	VC, VB, C#, VB.NET, JAVA
Database	Microsoft Access ( Sample )
Encryption	256 bit AES
Operating System	Windows 8, 7, Vista, XP, Server 2003/2008 Linux (Ubuntu, Devian, Fedora, OpenSUSE, Cent OS) ( Selected version only )

## Suprema Inc.

16F Parkview Tower, Jeongja, Bundang, Seongnam, Gyeonggi, 463-863 Korea

Tel : +82-31-783-4502, Fax : +82-31-783-4503

E-mail : sales@supremainc.com Homepage : www.supremainc.com

