

OMNIKEY® 5321 CL USB Reader

Contactless USB smart card reader

- ▶ **Versatile Applications** – Ideal for end-user environments with different contactless smart card technologies and tags in use
- ▶ **Fast Contactless Transmission** – Supports contactless smart cards up to 848 Kbps in fastest ISO 14443 A/B
- ▶ **Designed for User Convenience** – Housing design is optimized for advanced contactless applications
- ▶ **Readily compliant** – Supports HID® iCLASS® and MIFARE® as well as ISO 14443A/B and ISO 15693



ACCESS quality.

Housed in a robust closed housing with a convenient card retainer, the OMNIKEY® 5321 CL represents the ideal reader for contactless technology applications. Featuring a PC-linked reader that reads/writes to 13.56 MHz contactless smart cards in all three HF standards, the OMNIKEY 5321 CL economically supports end-user environments where a variety of contactless cards and tags are used.

Utilizing contactless smart card technology for PC-linked applications, the OMNIKEY® 5321 CL device allows users to experience the convenience, speed and security of contactless technology for applications, including logon to Windows®, networks, web sites and applications for the secure storage of user names, passwords and personal information.

- ▶ Supports three ISO standards for contactless cards (ISO 14443 A/B and 15693) and Microsoft WHQL
- ▶ Reader supports contactless smart cards with up to 848 Kbps in the fastest ISO 14443 transmission mode
- ▶ Standard application interfaces include PC/SC, Synchronous-API (on top of PC/SC), OCF (Open Card Framework) or CT-API

Contactless smart cards supported:

- ▶ HID: iCLASS®
- ▶ NXP: MIFARE®, DESFire®, SMART-MX and ICODE
- ▶ Texas Instruments: TagIT®
- ▶ ST Micro: x-ident, SR 176, SR 1X 4K
- ▶ Infineon: My-d (in secure mode UID only)
- ▶ Atmel: AT088RF020
- ▶ KSW MicroTech: KSW TempSens
- ▶ iCODE SLI, iCODE SL2 & LRI 64
- ▶ Contactless 2048 bit key generation in RSA mode (JCOP / SMART-MX)

For actual driver downloads please visit www.hidglobal.com/omnikey

Specifications

Base Model Number	OMNIKEY® 5321
Dimensions	3.78" x 3.07" x .031" (115 x 96.5 x 25.5 mm)
Weight	Approx. 5.64 oz / 160 g
Power supply	Bus powered
Operating temperature	32°-131° F (0° - 55° C)
Operating humidity	10-90% rH
HOST INTERFACE	
Host Interface	USB 2.0 (also compliant with USB 1.1)
Transmission speed	12 Mbps (USB 2.0 full speed)
CONTACTLESS SMART CARD INTERFACE	
Protocols	T=CL, MIFARE®, iCLASS® / ISO 14443 A with 848 Kbps transmission rate (depending on card) ISO 14443 B with 848 Kbps transmission rate (depending on card) ISO 15693 with 26 Kbps transmission rate (depending on card)
Supported APIs	PC/SC driver (ready for 2.01), Synchronous API (on top of PC/SC))
PC/SC Driver Support	Windows® 2000 / XP (32bit), 2003 Server, 2008 Server Windows® CE 5.0 / 6.0 / CE.NET (depending on hardware), Windows® XP 64bit (AMD64, EM64T, IA64), Windows® Vista (32bit / 64bit), Windows 7 (32bit/64bit) Linux® (in preparation), Mac® OS X 10.5 Leopard
Status indicator	Dual color LED (green=ready, red=busy)
Reader Board	Also available as PCB
Color	Dark grey
Options	Customer Specific Logo: Available upon request
Composition	ABS
Connector cable	70.9" (180 cm)
Meantime between failure (MTBF)	500,000 hours
Compliance / Certification	Microsoft® WHQL ¹ , USB 2.0 (USB 1.1 compatible), GSA FIPS 201 approved product list (in preparation)
Safety / Environmental	CE, FCC, UL, RoHS, WEEE
Warranty	Two year manufacturer's warranty. (For drivers, see complete lifetime support policy.)

¹ = Windows® Hardware Quality Lab.



© 2010 HID Global Corporation. All rights reserved. HID, the HID logo, Omnikey and the Omnikey logo are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 07/2010

MKT-OMNIKEY_5321_CL_DS_EN Rev. 07/2010



ACCESS experience.

hidglobal.com

HID Global Offices:

Corporate North America
15370 Barranca Pkwy
Irvine, CA 92618
U.S.A.
Tel: 1 800 237 7769
Tel: +1 949 598 1600
Fax: +1 949 598 1690

Asia Pacific
19/F 625 King's Road
North Point
Island East
Hong Kong
Tel: +852 3160 9800
Fax: +852 3160 4809

Latin America
Circunvalación Ote. #201 B
Despacho 2
Col. Jardines del Moral
Leon 37160, Gto.
Mexico
Tel: +52 477 779 1492
Fax: +52 477 779 1493

Europe, Middle East & Africa
Haverhill Business Park
Phoenix Road
Haverhill, Suffolk
CB9 7AE
England
Tel: +44 1440 714 850
Fax: +44 1440 714 840